

LUXANO 2 VARIO



Now it's VARIO!

LUXANO 2 with variably adjustable luminous flux

 **SCHUCH**

LUXANO 2 VARIO – ECONOMICAL AND FLEXIBLE

One single LED light fitting replaces conventional fluorescent lamps up to 2x58W. This solution offers high flexibility and high economic efficiency due to a maximum standardisation combined with an optimal stock management. You can adjust the luminous flux to the particular lighting situation on site without the need of any tools. Even afterwards illumination adaptations to changed lighting requirements are possible at any time. The right light fitting will be always ready to hand.

CONVINCING ADVANTAGE

- **Can be used universally** thanks to variable luminous flux setting as required
- **Tool-free adjustment** quickly and easily on site
- **Can be changed at any time**, e.g. when changing the utilisation of the premises with changed requirements for the lighting level
- **Reduction in the variety of types**, maximum standardisation, most economical storage
- **And now even more efficient** up to 152 lm/W

FURTHER VARIO VARIANTS

- **FC** – Fully pre-assembled for highspeed installation
- **HE** – Highly efficient design for reduced energy consumption
- **AUS** – For unprotected outdoor areas
- **IFS** – For food areas (International Featured Standard Food/HACCP)



Type	Connected load [W]	Luminous flux [lm]	Luminous efficacy [lm/W]	Tmax [°C]	Substitute for ²
167 12LG2 VARIO	18	2.700	150	35	> 1 x 36 W
	21	3.100	148	35	< 1 x 58 W
	26	3.800	146	35	> 1 x 58 W
	30	4.300 ¹	143	35	2 x 36 W
167 15LG2 VARIO	25	3.800	152	35	> 1 x 58 W
	29	4.400	152	35	2 x 36 W
	36	5.400	150	35	< 2 x 58 W
	43	6.200 ¹	144	35	2 x 58 W

Rounded values, technical developments reserved.

¹ Factory setting ² The given information is for rough orientation only. In each individual case a lighting calculation is necessary.

Further Infos:



Article details



LUXANO 2
variant diversity